

6 SPECIFICATIONS

Primary reduction ratio		2.48 (57/23)
Final reduction ratio		2.38 (38/16)
Overall drive ratio		5.23 (@Top gear)
Electrical Equipment		
Generator (Dynamo)		Nippon Denso ACQ104
Regulator		Nippon Denso ANSB02
Ignition coil		Nippon Denso AJPG36
Battery		Nippon Denchi GM14Z-3A (12V 14AH)
Starter		Mitsuba SM-224
Headlight type	US	Sealed Beam
	European	Semi-sealed
Headlight	US	12V 50/35W
	European	12V 45/40W
Tail/Brake light	US	12V 8/27W (3/32 CP)
	European	12V 5/21W
Speedometer light		12V 3.4W
Tachometer light		12V 3.4W
Neutral indicator light		12V 3.4W
High beam indicator light		12V 3.4W
Turn signal lights	US	12V 23W
	European	12V 21W
Turn signal indicator light		12V 3.4W
Oil pressure indicator light		12V 3.4W
Brake light failure indicator light		12V 3.4W
Horn		12V 2.5A
City light	European	12V 4W
Frame		
Type		Tubular, double cradle
Steering angle		39° to either side
Castor		63.5°
Trail		105 mm
Tire size	Front	3.25H-19 4PR
	Rear	4.00H-18 4PR
Suspension	Front	Telescopic Fork
	Rear	Swing arm
Suspension stroke	Front	140 mm
	Rear	80 mm
Front fork oil capacity (each fork)		171~180 cc
Front fork oil type		SAE 10W20
Brakes		
Type	Front and Rear	Disc brake
Effective disc diameter	Front	245 mm
	Rear	230 mm

Specifications subject to change without notice, and may not apply to every country.